

NPP Status




- Spacecraft in normal Mission Mode, all systems nominal
- Ground System performance nominal with data flowing to NESDIS and AFWA Centrals and to CLASS archive
- All Instruments are in normal operational mode
 - -ATMS SDR data declared provisional (ready for broader use)
 - —ATMS SDR/TDR to be used operationally by NOAA NCEP (NWP center) in April 2012
 - -VIIRS, CrIS, OMPS, and CERES Instrument Commissioning is continuing



Suomi - NPP Images








Revised Commissioning Schedule








VIIRS M05/M04/M03 (red/green/blue) VIIRS M15 (10.76 microns)








Resolution Improvements: OLS vs. DNB






- → 740 m instantaneous geometric field of view (DNB) vs. ~5 km for the OLS results in dramatic spatial resolution improvements.
- → DNB Imagery courtesy of Steven Miller CIRA/CSU



Resolution Improvements: OLS vs. DNB






- → 740 m instantaneous geometric field of view (DNB) vs. ~5 km for the OLS results in dramatic spatial resolution improvements.
- → DNB Imagery courtesy of Steven Miller CIRA/CSU



VIIRS M07 (0.865 microns) grey scaled 19 January 2012






- VIIRS Data Anomaly
- •Degradation in M7/I2 observed after launch.
- Smaller effect in M6 & M5.
- •Commissioning paused while anomaly was studied.
- •Degradation believed to be caused by an error in mirror coating process. An inadvertent layer of tungsten film was put on telescope mirrors.
- Commissioning resumed Jan 18
- Degradation is slowing, should level off.
- •No effect on VIIRS data products; VIIRS SNR in M7 expected to be above spec.



VIIRS Anomaly Change in VIIRS Solar Data as a function orbit number





F is conversion factor that compares the measured VIIRS solar data to the predicted value. Data shows 1/F-factor. Should be 1 for new instrument.


Test periods used to diagnose VIIRS anomaly.

Data show anomaly depends on solar exposure; increases with light; stops in dark.



VIIRS Anomaly Change in VIIRS Solar Data as a function of UV exposure





Anomaly depends on exposure to light, probably in the UltraViolet

Calculate amount of UV exposure in each orbit. Replot data, converting x-axis from orbit number to UV exposure time.


1 day UV exposure = 6.5 calendar

Data shows smooth dependence



VIIRS Anomaly Predict Amount of Change in VIIRS using Solar Data





1 day UV exposure = 6.5 calendar days.

For M7/I2 865 nm High Gain Signal-to-Noise (SNR)

	SNR	Margin
Specification	215	
Raytheon	419	95%

Analyze with a simple predictive optical model of multiple mirrors with an absorbing coating.

Model predicts throughput reduced to 81%

	SNR	Margin	
djusted Raytheon	339	58%	


Gov't estimates of VIIRS SNR are higher than Raytheon's.

Raytheon producing more sophisticated predictive optical model of VIIRS degradation.



SWIR Degradation Estimated based on Witness #2 UV Exposure


RaytheonSpace and Airborne Systems





SWIR Turn-on shows expected performance

RaytheonSpace and Airborne Systems



Error Bars are +/-13% of predicted gain

- Original based sensor-TV, nominal plateau RC2 P2
- Degraded thruput reduces original by 24 hr UV exposure results for Witness#2



Questions?



